

TECHNICAL SPECIFICATIONS B9100

B9000 SERIES - HOLLOW CORE DOORS WOOD

For regular usage (indoor only)



Mill Option (MO)

Specifications	Description
Size :	Maximum: 1 219 mm x 2438 mm (48 "x 96"). Others on request.
Thickness :	35 mm (1-3/8 "), 44 mm (1-3/4 ").
Stiles :	36 mm (1 7/16 ") of low density wood, finger jointed clear pine (MO).
Rails :	36 mm (1 7/16 ") of low density wood, finger jointed knotty or clear pine or LSL.
Core :	Hollow core of 120 mm (4 3/4") at manufacturer's choice. Available NAUF/FSC.
Faces :	Plywood (choice of species, 2 ply only), hardboard panel or plastic laminate bonded to rigid crossband. Available FSC, NAUF and NAUF/FSC.
Adhesive :	Type 2, fully weatherproof; PVA polyvinyl acetate (NAUF); VOC < 14.98 g/L.
Options :	Custom doors on request. Bifolds doors, sliding doors, retractable (pocket doors). Doors with low VOC primer. Stiles and rails with primer or sealed. Individual identification (tag). Delivery by floor.
Finish :	Clear varnish, stain, opaque paint or primer only. The top and bottom are sealed. Development of custom colors.
LEED	Boccam attests that these models of particleboard core doors contribute to industry programs such as LEED ® , Green Globes and others, contact us!
Standard :	ANSI/WDMA I.S. 1A – 2013 ; CAN/CSA 0132.2 Series-90(R1998) AWI/AWMAC WI 2nd Edition, October 1, 2014
Warranty :	Covered by a limited warranty of 1 year against manufacturing defects. Please contact us for more details on our warranty.

Note : The stiles and rails dimensions are untrimmed. These dimensions will vary according to the fit of the finished dimensions.
For more information, consult the Technical Data Chart.