

## TECHNICAL SPECIFICATIONS B9200

### B9000 SERIES - HOLLOW CORE DOORS WOOD

For intensive usage (indoor only)



Mill Option (MO)  
Compatible Edge (CE) /  
Matching Edge (ME)

Specifications	Description
<b>Size :</b>	Maximum: 1 219 mm x 3048 mm (48 "x 120").
<b>Thickness :</b>	35 mm (1-3/8 " ), 44 mm (1-3/4 " ).
<b>Stiles :</b>	22 mm (7/8") of hard wood (MO,CE ou ME) glued to 42 mm (1-5/8") of LSL (Laminated Strand Lumber) or clear finger jointed pine. (Total : 64 mm (2-1/2"))
<b>Lock Block :</b>	Lock materials of low-density wood parts or particleboard of 76mm x 356 mm (3" x 14"). (not including stile).
<b>Rails :</b>	42 mm (1-5/8") of low density wood, finger jointed knotty or clear pine or LSL
<b>Core :</b>	Hollow core of 120 mm (4 3/4") at manufacturer's choice. Available NAUF/FSC.
<b>Faces :</b>	Plywood (choice of species, 2 ply only), hardboard panel or plastic laminate bonded to rigid crossband. Available FSC, NAUF and NAUF/FSC.
<b>Adhesive :</b>	Type 2, fully weatherproof; PVA polyvinyl acetate (NAUF); VOC < 14.98 g/L.
<b>Options :</b>	Custom doors on request. Bifolds doors, sliding doors, retractable (pocket doors). Doors with low VOC primer. Stiles and rails with primer or sealed. Individual identification (tag). Delivery by floor.
<b>Finish :</b>	Clear varnish, stain, opaque paint or primer only. The top and bottom are sealed. Development of custom colors.
<b>LEED</b>	Boccam attests that these models of particleboard core doors contribute to industry programs such as LEED ® , Green Globes and others, contact us!
<b>Standard :</b>	ANSI/WDMA I.S. 1A – 2013 ; CAN/CSA 0132.2 Series-90(R1998) AWI/AWMAC WI 2nd Edition, October 1, 2014
<b>Warranty :</b>	Covered by a limited warranty of 1 year against manufacturing defects. Please contact us for more details on our warranty.

Note : The stiles and rails dimensions are untrimmed. These dimensions will vary according to the fit of the finished dimensions.  
For more information, consult the Technical Data Chart.